




SPECIFICATIONS	47100 COPPER WIRE STRIPPER CWS-1	47200 COPPER WIRE STRIPPER CWS-2	47030 COPPER WIRE STRIPPER JR
UPC:	625912471009	625912472006	625912470309
Motor size:	1 HP	1/2 HP	Drill operated: Max 300 RPM.
Wire Range:	14 AWG to up to 3" in diameter	14AWG to 750MCM (1-1/4" Max)	14 AWG – 4/0. NMSC 14 AWG – 10 AWG.
Product Material	Aluminum frame	Aluminum frame	Aluminum frame
Blade Material:	Tool steel	Tool steel	Tool steel
Strips:	Solid core or braided wire	Solid core or braided wire	Solid core or braided wire
Replacement parts:	BLADE PART# 47100B RED FEED GUIDE PART# 47100G BOTTOM PULLING GEARS PART# 47100W	BLADE PART# 47200B or 47200B-2 RED FEED GUIDE PART# 47200G BOTTOM PULLING GEARS PART# 47200W	BLADE PART# 47030B RED FEED GUIDE PART# 47030G BOTTOM PULLING GEARS PART# 47030W
Product Weight:	90LBS	45LBS	3.85LBS
	CWS-1 Product Features: <ul style="list-style-type: none"> - CSA and UL approved. - Blade easily re-sharpened. - Fully adjustable wire guide. - Bench model – Anti-slip base. - Made in Canada. - Hardened one piece blade. - Not TAA compliant. 	CWS-2 Product Features: <ul style="list-style-type: none"> - CSA and UL approved. - Blade easily re-sharpened. - Fully adjustable wire guide. - Bench model – Anti-slip base. - Made in Canada. - Hardened one piece blade. - Not TAA compliant. 	JR Product Features: <ul style="list-style-type: none"> - Hardened one piece blade - Blade easily re-sharpened - Fully adjustable wire guide - Made in Canada - TAA compliant.