



TOP HAT - TECHNICAL SPECS

HVQC4

THE HIGH VOLUME QUICK COVER IS A NONMETALLIC VOLUME COVER DESIGNED TO FIT INDUSTRY STANDARD 4" SQUARE JUNCTION BOXES IN DRY LOCATIONS.

MATERIAL: FLAME RESISTANT POLYCARBONATE

TEMP RANGE: -30F to 260F

DEMISSION: 4X4X4

THICKNESS: 2.3mm

VOLUME: 35.8 CUBIC INCHES

WEIGHT: 4.2oz

COMPLIANCE

UL FILE NUMBER – E476148

UL STANDARD – 2043

UL 2043 STANDARD FOR FIRE TEST FOR HEAT AND VISIBLE SMOKE RELEASE FOR DISCRETE PRODUCTS AND THEIR ACCESSORIES INSTALLED IN AIR-HANDLING SPACES - Edition 4 - Issue Date 2013/10/02

UL STANDARD - 514C

UL 514C STANDARD FOR NONMETALLIC OUTLET BOXES, FLUSH-DEVICE BOXES, AND COVERS - Edition 4 - Revision Date 2014/12/10

CSA STANDARD - CSA C22.2 No. 18.2

CSA C22.2 No. 18.2 STANDARD FOR NON-METALLIC OUTLET BOXES

NEC (NFPA-70) 300.22 (C) (D)

SUITABLE FOR USE IN AIR HANDLING SPACES