

<b>Product Name</b>	Slammers Rigid/PVC Conduit Cap
<b>Brand</b>	<b>RACK-A-TIERS</b>
<b>Part Number</b>	35075.RCC
<b>UPC</b>	625912350755

Product Weight and Package Dimensions	
<b>Product Weight</b>	2.75lbs
<b>Product Dimensions (L x W x H)</b>	3/4"
<b>Product Package Dimensions (L x W x H)</b>	10" X 14" X 5"

<b>Product Material</b>	ABS Plastic
<b>Product Type</b>	Conduit Caps for Concrete Pours
<b>Colour</b>	Red
<b>Quantity</b>	50 pieces per bag

**Product Features**  
**Lock your rigid or PVC conduit in place during concrete pours**

- Made in the USA.
- Available in 3/4" and 1" sizes to fit Schedule 40 Metal or PVC.
- PROTECT – Slammers Conduit Caps are the best way to protect your conduit systems. No other method is as effective at keeping rocks, concrete, and other construction debris from getting into your conduit.
- SIMPLE – These rigid and PVC conduit caps are even easier to use than duct tape. Just slam them on and you're good to go. The tapered design guarantees a secure fit you can trust.
- DURABLE – Slammers are made of high-quality ABS plastic that can withstand even the harshest job sites and elements.
- CLEAN – Take pride in your work by using the Slammers Cap & Spacer system for an install that will make others jealous. Designed specifically with 4-square boxes in mind, you can be sure you'll get the perfect fit every time.

General Information				
<b>General</b>				
Ashland Product Code	* 4030501			
Material Status	* Commercial: Active			
Availability	* North America			
Test Standards Available	* ASTM			
Recycled Content	* No			
Features	* Easy flowing , Heat and impact resistance, RoHS compliant			
Forms	* Pellets			
Processing Method	* Injection			
Properties				
	Nominal Value	Unit	Test Method	
Melt Volume -Flow Rate (MVR) (230 °C/3.8 kg)	4.8	cm <sup>3</sup> /10min	ASTM D1238	
Melt Volume-Flow Rate (MVR) (220°C/10 kg)	19	cm <sup>3</sup> /10min	ASTM D1238	
Density	1.04	g/cm <sup>3</sup>	ASTM D1505	
<b>Mechanical</b>				
	Nominal Value	Unit	Test Method	
Tensile Modulus	333,000	psi	ASTM D638	
Tensile Strength@ Yield	6,520	psi	ASTM D638	
Flexural Modulus	333,000	psi	ASTM D790	
Flexural Strength	9,430	psi	ASTM D790	
<b>Impact</b>				
	Nominal Value	Unit	Test Method	
Notched Izod (73°F)	5.6	ft-lb/in	ASTM D256	
Charpy Impact Strength	*	kJ/m <sup>2</sup>	ISO 179	
<b>Hardness</b>				
	Nominal Value	Unit	Test Method	
Rockwell	103	R	ASTM D785	
<b>Thermal</b>				
	Nominal Value	Unit	Test Method	
Vicat, A/2 (50 deg, C/h, 50N)	204	°F	ASTM D1525	
Deflection Temperature of Plastic @ 66 psi	195	°F	ASTM D648	
Deflection Temperature of Plastic @ 264 psi	172	°F	ASTM D648	
Optical	Nominal Value	Unit	Test Method	
	*			
<b>UL Information</b>				
	Nominal Value	Unit	Test Method	
Flammability Rating @ 0.031	HB	---	UL 94	
Flammability Rating @ 0.059	HB	---	UL 94	
Flammability Rating @ 0.118	HB	---	UL 94	

**Suggested Applications**  
Rigid thin walled containers, sports and leisure , toys, Housewares, Molded caps and closures

**Other Properties**

**Compliance**  
Hival ABS HG6 Natural meets the requirements of the "Federal Food, Drug and Cosmetic Act" and all applicable "Food Additive Regulations" including 21 CFR 181.32 "Acrylonitrile copolymers and resins". The products may only be used in repeated use applications and not in contact with food containing alcohol. Compliance to extractive limitations is the responsibility of the article manufacturer (21 CFR 181.32(b)).

