

SPECIALTY ELECTRICAL TOOLS





SPECIFICATIONS	RAT500	RAT500.B2	RAT500.B4	RAT750	TT500	TT500.B2	TT500.B4
© US MC 219640			Residence of the second of the			III C	11100 (3.1
Product UPC:	625912170506	625912170520	625912170544	625912170759	625912514874	625912920026	625912500044
Measurements:	1/2"	1/2"	1/2"	3/4"	2-way 1/2"	2-way 1/2"	2-way 1/2"
Packaged Dimensions:	8" x 8" x 3.5"	7¾" x 6" x 8¼"	9 7/8" x 8" x10"	8" x 8" x 3.5"	8" x 8" x 3.5"	7¾" x 6" x 8¼"	9 7/8" x 8" x 10"
Packaged Weight:	0.90 LBS	1.90 LBS	4.20 LBS	0.64 LBS	0.90 LBS	2 LBS	3.85 LBS
Product Material:	Plastic	Plastic	Plastic	Plastic	Plastic	Plastic	Plastic
Product Type:	Connectors	Connectors	Connectors	Connectors	Connectors	Connectors	Connectors
Quantity:	100	200	400	50	100	200	400
Country of Origin:	Canada	Canada	Canada	Canada	Canada	Canada	Canada
Single Cables:	12/3, 10/3, 10/2	12/3, 10/3, 10/2	12/3, 10/3, 10/2	8/3, 6/3	12/3, 10/2, 10/3	12/3, 10/3, 10/2	12/3, 10/3, 10/2
1 or 2 Cables:	14/2, 14/3, 12/2	14/2, 14/3, 12/2	14/2, 14/3, 12/2	Not Applicable	14/2, 14/3, 12/2	14/2, 14/3, 12/2	14/2, 14/3, 12/2

## **Product Features**

The TT500 is a NMSC/Romex connector that installs from inside and outside the box. Suitable for all 1/2 in. knockouts. Fast and Easy. No tools required. Just squeeze and snap them into the desired knockout to secure your wires as they enter the enclosure. Tom 2-Way Romex connectors are perfect for old work and new work. They're especially helpful in retrofit situations.

The RAT500 (1/2") and RAT750 (3/4") are NMSC connectors.

- Snaps into place in 2 seconds, saving time and labour costs
- Easily removed from knockouts
- Easy removal of Non-Metallic cable from connectors (1 or 2 wires)
- Easily installed in confined and tight areas i.e. down lights, panels close to studs and high ceiling installations
- The RAT500, RAT750 and TT500 are UL & CSA approved
- 1 or 2 wires (RAT750 is 1 wire only)
- 60 lb. pull test
- V0 fire rating







