

Product Name	Slammers Rigid/PVC Conduit Cap
Brand	RACK-A-TIERS
Part Number	35100.RCC
UPC	625912351004

Product Weight and Package Dimensions	
Product Weight	2.75lbs
Product Dimensions (L x W x H)	1"
Product Package Dimensions (L x W x H)	10" X 14" X 5"

Product Material	ABS Plastic
Product Type	Conduit Caps for Concrete Pours
Colour	Blue
Quantity	50 pieces per bag

Product Features
Lock your rigid or PVC conduit in place during concrete pours

- Made in the USA.
- Available in ¾" and 1" sizes to fit Schedule 40 Metal or PVC.
- PROTECT – Slammers Conduit Caps are the best way to protect your conduit systems. No other method is as effective at keeping rocks, concrete, and other construction debris from getting into your conduit.
- SIMPLE – These rigid and PVC conduit caps are even easier to use than duct tape. Just slam them on and you're good to go. The tapered design guarantees a secure fit you can trust.
- DURABLE – Slammers are made of high-quality ABS plastic that can withstand even the harshest job sites and elements.
- CLEAN – Take pride in your work by using the Slammers Cap & Spacer system for an install that will make others jealous. Designed specifically with 4-square boxes in mind, you can be sure you'll get the perfect fit every time.

General Information			
General			
Ashland Product Code	* 4030501		
Material Status	* Commercial: Active		
Availability	* North America		
Test Standards Available	* ASTM		
Recycled Content	* No		
Features	* Easy flowing , Heat and impact resistance, RoHS compliant		
Forms	* Pellets		
Processing Method	* Injection		
Properties			
Melt Volume -Flow Rate (MVR) (230 °C/3.8 kg)	Nominal Value	Unit	Test Method
	4.8	cm ³ /10min	ASTM D1238
Melt Volume-Flow Rate (MVR) (220°C/10 kg)	19	cm ³ /10min	ASTM D1238
Density	1.04	g/cm ³	ASTM D1505
Mechanical			
	Nominal Value	Unit	Test Method
Tensile Modulus	333,000	psi	ASTM D638
Tensile Strength@ Yield	6,520	psi	ASTM D638
Flexural Modulus	333,000	psi	ASTM D790
Flexural Strength	9,430	psi	ASTM D790
Impact			
	Nominal Value	Unit	Test Method
Notched Izod (73°F)	5.6	ft-lb/in	ASTM D256
Charpy Impact Strength	*	kJ/m ²	ISO 179
Hardness			
	Nominal Value	Unit	Test Method
Rockwell	103	R	ASTM D785
Thermal			
	Nominal Value	Unit	Test Method
Vicat, A/2 (50 deg, C/h, 50N)	204	°F	ASTM D1525
Deflection Temperature of Plastic @ 66 psi	195	°F	ASTM D648
Deflection Temperature of Plastic @ 264 psi	172	°F	ASTM D648
Optical	Nominal Value	Unit	Test Method
	*		
UL Information			
	Nominal Value	Unit	Test Method
Flammability Rating @ 0.031	HB	---	UL 94
Flammability Rating @ 0.059	HB	---	UL 94
Flammability Rating @ 0.118	HB	---	UL 94

Suggested Applications
Rigid thin walled containers, sports and leisure , toys, Housewares, Molded caps and closures

Other Properties

Compliance
Hival ABS HG6 Natural meets the requirements of the "Federal Food, Drug and Cosmetic Act" and all applicable "Food Additive Regulations" including 21 CFR 181.32 "Acrylonitrile copolymers and resins". The products may only be used in repeated use applications and not in contact with food containing alcohol. Compliance to extractive limitations is the responsibility of the article manufacturer (21 CFR 181.32(b)):

