

RACK-A-TIERS®

SPECIALTY ELECTRICAL TOOLS



SPECIFICATIONS



Product Name	Slammers Rigid/ PVC Conduit Cap 1"	Slammers Rigid/ PVC Conduit Spacer 1"	Slammers Rigid/ PVC Conduit Spacer 1" with support hole	Slammers Rigid/ PVC Conduit Cap 3/4"	Slammers Rigid/ PVC Conduit Spacer 3/4"	Slammers Rigid/ PVC Conduit Spacer 3/4" with support hole
Brand	Rack-A-Tiers	Rack-A-Tiers	Rack-A-Tiers	Rack-A-Tiers	Rack-A-Tiers	Rack-A-Tiers
Part Number	35100.RCC	35100.RCS	35100.RSWS	35075.RCC	35075.RCS	35075.RSWS
UPC	625912351004	625912351011	625912351028	625912350755	625912350762	625912350779
Product Weight	0.0615lbs	0.0385lbs	0.0485lbs	0.0515lbs	0.0345lbs	0.0430lbs
Product Dimensions (L x W x H)	3.375" x 1.625" x 1" Inside diameter 1"	3.25" x 1.625" x 1" Inside diameter 1"	3.25" x 2.25" x 1" Inside diameter 1"	3.125" x 1.375" x 1" Inside diameter: 3/4"	3" x 1.375" x 1" Inside diameter: 3/4"	3"x 2.125" x 1" Inside diameter: 3/4"
Product Package Dimensions (L x W x H)	10" X 15" X 5"	10" X 15" X 5"	10" X 15" X 5"	10" X 15" X 5"	10" X 15" X 5"	10" X 15" X 5"
Product Package Weight	3.3 lbs	2.23lbs	2.23lbs	2.75lbs	2.24lbs	2.24lbs
Quantity	50 pieces per bag	50 pieces per bag	50 pieces per bag	50 pieces per bag	50 pieces per bag	50 pieces per bag
Product Material	ABS Plastic	ABS Plastic	ABS Plastic	ABS Plastic	ABS Plastic	ABS Plastic
Product Type	Conduit caps for concrete pours	Conduit spacers for concrete pours	Conduit spacers for concrete pours	Conduit caps for concrete pours	Conduit spacers for concrete pours	Conduit spacers for concrete pours
Colour	Blue	Blue	Blue	Red	Red	Red
Country of Origin	USA	USA	USA	USA	USA	USA

Product Features

Lock your rigid or PVC conduit in place during concrete pours

- Available in 3/4" and 1" sizes to fit Schedule 40 Metal or PVC.
- PROTECT – Slammers Conduit Caps are the best way to protect your conduit systems. No other method is as effective at keeping rocks, concrete, and other construction debris from getting into your conduit.
- SIMPLE – These rigid and PVC conduit caps are even easier to use than duct tape. Just slam them on and you're good to go. The tapered design guarantees a secure fit you can trust.
- DURABLE – Slammers are made of high-quality ABS plastic that can withstand even the harshest job sites and elements.
- CLEAN – Take pride in your work by using the Slammers Cap & Spacer system for an install that will make others jealous. Designed specifically with 4-square boxes in mind, you can be sure you'll get the perfect fit every time.

Additional Features for Conduit Spacer with Support hole

- Support hole for 3/8" rebar.
- EXTRA SUPPORT – This version of the Slammers spacers has a built-in support hole for use with precut rebar. The extra hole is designed for a 3/8" rebar stake.
- PRECISION – Take pride in your work by using the Slammers Cap & Spacer system for an install that will make others jealous. Designed specifically with 4-square boxes in mind, you can be sure you'll get the perfect fit every time.



FOLLOW US ON



WWW.RACK-A-TIERS.COM

SALES@RACK-A-TIERS.COM

TOLL FREE: 1 (888) 939-9991



SPECIALTY ELECTRICAL TOOLS

HIVAL ABS HG6 NAT



HIVAL*RESINS

Hival ABS HG6 Natural Ashland Distribution -ABS

General Information

General

Ashland Product Code	* 4030501
Material Status	* Commercial: Active
Availability	* North America
Test Standards Available	* ASTM
Recycled Content	* No
Features	* Easy flowing , Heat and impact resistance, RoHS compliant
Forms	* Pellets
Processing Method	* Injection

Properties

	Nominal Value	Unit	Test Method
Melt Volume -Flow Rate (MVR) (230 °C/3.8 kg)	4.8	cm³/10min	ASTM D1238
Melt Volume-Flow Rate (MVR) (220°C/10 kg)	19	cm³/10min	ASTM D1238
Density	1.04	g/cm³	ASTM D1505
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	333,000	psi	ASTM D638
Tensile Strength@ Yield	6,520	psi	ASTM D638
Flexural Modulus	333,000	psi	ASTM D790
Flexural Strength	9,430	psi	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod (73°F)	5.6	ft-lb/in	ASTM D256
Charpy Impact Strength	*	kJ/m²	ISO 179
Hardness	Nominal Value	Unit	Test Method
Rockwell	103	R	ASTM D785
Thermal	Nominal Value	Unit	Test Method
Vicat, A/2 (50 deg, C/h, 50N)	204	°F	ASTM D1525
Deflection Temperature of Plastic @ 66 psi	195	°F	ASTM D648
Deflection Temperature of Plastic @ 264 psi	172	°F	ASTM D648
Optical	Nominal Value	Unit	Test Method
	*		
UL Information	Nominal Value	Unit	Test Method
Flammability Rating @ 0.031	HB	---	UL 94
Flammability Rating @ 0.059	HB	---	UL 94
Flammability Rating @ 0.118	HB	---	UL 94

Suggested Applications

Rigid thin walled containers, sports and leisure , toys, Housewares, Molded caps and closures

Other Properties

Compliance

Hival ABS HG6 Natural

meets the requirements of the "Federal Food, Drug and Cosmetic Act" and all applicable "Food Additive Regulations" including 21 CFR 181.32 "Acrylonitrile copolymers and resins". The products may only be used in repeated use applications and not in contact with food containing alcohol. Compliance to extractive limitations is the responsibility of the article manufacturer (21 CFR 181.32(b)):



FOLLOW US ON



WWW.RACK-A-TIERS.COM

SALES@RACK-A-TIERS.COM

TOLL FREE: 1 (888) 939-9991